



Service • Support • Success

Ideal for polishing projects less than 1,000 sq. ft. (or wherever Efficient edge Grinding is Required)

C = concrete

T = terrazzo

M = marble

PM-431

Prep Master®



Specifications

Motor	5 HP - 3 or 1 Phase
Power Source	230 VAC 3 Phase 60 /50Hz
Current	17 Amps Soft Start
Motor RPM	2625 rpm @ 90 Hz
Power Cord	25 ft. (4-12)
Vacuum Hose	2 in. x 25 ft. x Two
Weight	275 lbs.
Tool RPM	1,500 rpm @ 90 Hz
Pressure on Tools	350 lbs. w/Weights
Tools Available	PCD's, Metal bond, Resin
Dimensions	24"-56" L x 17" W x 52" H
Cleaning Path	17"
Recommended Vacuum	Planet Vac or Equivalent



Production Rates

Mastic Removal Rates:
200 sq. ft. / hr.

Thin Set Removal Rates:
250 sq. ft. / hr.

Mil Coatings Removal Rates:
150 sq. ft. / hr.

Concrete Polishing Rates:
250 sq. ft.

Distributed by



(800) 945-4016 Mid-West
 (800) 964-6006 North-West
 (877) 995-9006 West-Coast
 info@surfaceprepsuperstore.com
 www.surfaceprepsuperstore.com

U.S. Standard Measurements

Price, availability and specifications subject to change without notice